





Doosan Infracore Construction Equipment

Doosan Light Towers

When your workday doesn't end, or your event heats up after the sun goes down, all you need is Doosan Light Source to work for you. With Doosan lighting solutions for darkness and enhance your productivity through our valued service.

Advantages:

- Single-handed easy operation of raising and lowering of tower in just minutes
- Fully extendable, 360° rotatable, tillable tower
- Easy transportation with 3 Light Source fitting in a single truck of 25 feet
- Easy maneuverability Lightest equipment in the market weighing less than a ton (without fuel).
- Easily tow-able at a speed of 30km/hr.
- 62 hours of continuous operation.
- Power-in and power-out option (available on premium model, generator option available)
- UV rays protected curly cord placed within its protection cover.
- High capacity Air Filter for dusty applications
- Patented, fool proof self locking winch
- Luminaries & electrical parts conform to NEMA 6.6 global standards
- · Flicker free metal halide white lights and brush less maintenance free alternator
- Can be easily handled with forklifts at job sites.
- One stop destination for complete service support.
- Sales Channel located across India with service area network within 150 kms
- Over 1000 light towers currently operational in mines, airports, industries, roads and civil
 construction works.

Specifications:

Model	LSP	DLS1600
Performance		
Luminaries	4000W	1600W
No. of bulbs	4 nos, 1000W each	4 nos, 400W each
Type of bulb	Metal Halide	Metal Halide
Tower height	9 meters	9 meters
Engine		
Rating	11.3 HP @ 1500 rpm	11 HP @ 3000 rpm
Make	Kubota	Mitsubishi
Model	D1105	L2E
Alternator	Single Phase (4 Pole)	Single Phase (2 Pole)
Make	Mecc Alte	Mecc Alte
Model	LT3-130/4	LT3-100/2
Frequency	50 Hz	50 Hz
Dimensions (Genera	ator set with Acoustic Enclosure)	
Overall Length	4475mm	4475mm
Overall Width	1560mm	1560mm
Overall Height	1700mm	1700mm
Overall Weight	978 Kgs	950 Kgs















Doosan Infracore Construction Equipment

Doosan Infracore India Pvt. Ltd 3rd Floor, TNPL Building, No: 67, Mount Road, Guindy, Chennai - 600032 Tel: +91 44 42223900; Fax: +91 44 42223905; Toll Free: 1800 200 2299 Email: marketingindia@doosan.com Website: www.doosaninfracore.com www.doosanportablepower.com