



Portable Power

## StonAIR Series

Pressure is Productivity



Doosan Infracore  
Construction Equipment

## StoneAir Series

Doosan "StoneAir Series" portable air compressor is the "Best in Class" for 2 jack ("StoneAir 2"), 3 jack ("StoneAir 3") hammer drilling. Compact, Quiet-running, Light Weight Design, Superior Running Gear and Fuel efficient Engine Ensures-Reliability, Safety and Efficiency.

### "Value for Money" Compressors :

- Fuel economy.
- Lowest operating cost in its class.
- High air-end life.
- Enhanced engine life.
- High Reliability.

### Performance Features :

- Better fuel economy.
- Patented air-end design – Superior volumetric efficiency, Enhanced life, Low engine rpm.
- Low engine rpm – Higher fuel efficiency and enhanced engine life.
- Specially blended lubricant – Extended warranty.
- Guaranteed pressure and flow at discharge valve.
- Best fit for 2 Jack hammer operation.
- Cool Box – Keeps the internal canopy temperature low – Improves components life.
- Polymer fuel tank – Corrosion and rust free, light weight.
- Height adjustable tow bar for easy towing at site with different vehicles.
- Easy transportation – Compact and light weight.

### Easy Serviceability :

- Lockable side doors for quick and easy access for service.
- Easy rear access encourages easy maintenance – for cleaning Radiator and Oil Cooler.
- Heavy duty single point lifting bail.

### Engineered with Safety :

- Integrated automatic safety and shut down features for engine and compressor under the following conditions
  - High discharge temperature.
  - Low engine oil pressure.
  - High engine water temperature.
- Auto blow down valve, safety valve, Air filter maintenance indicator.

### Specifications :

Compressor models	Unit	StoneAir 2	StoneAir 3
<b>Performance</b>			
Free Air Delivery*	CFM	260	340
Rated Operating Pressure	PSI	100	100
<b>Engine</b>			
Make	--	Ashok Leyland	Ashok Leyland
Model	--	W04D	W04CT
BHP	HP	78.4	101.3
Rated Speed	rpm	2400	2300
<b>Dimensions</b>			
Overall Length	mm	3535	3535
Overall Width	mm	1740	1740
Overall Height	mm	1850	1850
Gross Weight	kg	1470	1505
Max. Towing Speed	Km/hr	30	30

\*as per ISO 1217 Tolerance limit

\*Product improvement is a continuing goal at Doosan. Design and specifications are subject to change without notice or obligation.



**Doosan Infracore**  
Construction Equipment

**Doosan Infracore India Pvt Ltd.**

3rd Floor, TNPL Building, #67, Mount Road,

Guindy, Chennai - 600032, Tamilnadu, India

Ph: +91 44 42223900; Fax: +91 44 42223905;

Email: marketingindia@doosan.com Toll Free: 1800 200 2299

Website: www.doosanconstruction.com / www.doosaninfracore.com/india

### Authorized Dealer