







AIR CONDITIONED CABIN

13



One Tough Animal_™

S650 Turbo-Skid Steer Loader

Speci@cations:

\$650

Performance:

Rated Operating Capacity (SAE J732) ROC With 200 lb. Frame Mounted Counterweight Kit ROC With 300 lb. Frame Mounted Counterweight Kit Tipping Load (SAE) Hydraulic Pump Capacity High Flow Option Operating Weight (SAE) Travel Speed—Single Speed Travel Speed—Two Speed option Bucket Capacity (std)

2690 lbs. (1220 kg) 2840 lbs.(1288 kg)

2890 lbs.(1311 kg)

5380 lbs. (2440 kg) 23.0 GPM (87.1 L/min) @ high idle 30.5 GPM (115.5 L/min) @ high idle 8327 lbs. (3777 kg) 7.1 mph (11.4 km/hr) 7.1/12.3 mph (11.4/19.8 km/hr) 0.5 cu.m (17.6 cu.Ft)

Dimensions:

Length with Standard Bucket Height with Operator Cab Height to Bucket Hinge Pin Width (Over Standard Tires) Width (Over Bucket)

136.8" (3474 mm) 81.3" (2065 mm) 124.0" (3149 mm) 72.1" (1832 mm) 74" (1880 mm)

Engine:

Make/Model Emissions Tier (EPA) Fuel/Cooling Number of Cylinders Horsepower, (SAE Gross) Displacement Fuel Tank

Kubota/V3307-DI-TE3 Interim Tier IV Diesel/Liquid

74.3 HP (55.4 kW) 203 cu. in. (3.3 L) 27.3 gals. (103.3 L)

Operation:

Steering and Drive

Vehicle Steering - forward, reverse, travel speed and steering controlled by two independent hand levers. Raise / Lower Lift Arms and Bucket Dump / Rollback, Controlled by separate foot pedals or optional Advanced Control System (ACS) or optional Selectable Joystick Controls Hydrostatic Four-Wheel Drive

Transmission

Hydraulics

Standard Features:

- · Adjustable Cushion Seat
- Automatically Activated Glowplugs
 Bobcat Interlock Control System (BICSTM)
- Bob-Tach
- Standard Cab
- Dual Path Cooling System
- Engine/Hydraulic Shutdown
 Front Auxiliary Hydraulics
- · Front & Rear Lights

Lift Arm Support

- Gauges/Warning LightsOperator Brake
- · Seat Bar
- Seat Belt
- Tires: 12 x 16.5
- Turbo-Charger (Approved Spark Arrestor)
- Alarm Package (Backup Alarm and Horn)

Options/Accessories:

- · Advanced Control System (ACS)
- · Air Conditioning
- Attachment Control Kit
- · Bobcat Heavy-Duty Tyres
- Heavy Duty Óéset
- · Cab Enclosure
- Cab Heater
- Catalytic Puriller
- Counterweight · Solid Tires

- · Deluxe Instrument Panel · Flasher/Strobe/Rotating
- Beacon Lights
- Joystick Control
- Suspension Seat
 Hydraulic Bucket Positioning
- · High Flow Option
- Power Bob-Tach
- · Ride Control

Bobcat S650 Skid Steer Loader... Greater Performance, Visibility, Comfort and Value!

Bobcat

Greater Performance

Vertical-path lift arms deliver added performance on every jobsite:

- · More lift gapacity.
- · More lift height and reach for truck loading.

Greater Visibility

The low-pro⊡le, vertical-path lift arm design and innovative cab enhance the operator's view to key areas during operation: the sides, front and rear corners of the loader. Even with the optional front door, the S650 oeers good visibility. As any operator will tell you, a better view of the work area means greater egciency.

Greater Comfort

The cab is designed with the operator in mind, for optimum comfort and functionality. And with its larger opening and dual-tilt cylinder lift arm design, it's easy to enter and exit. The seat bar pivots from the rear, providing secondary restraint protection; it's also a comfortable armrest for operators of all sizes. Plus, the work light design doubles the amount of illumination to the work area for better operation in low-light areas.

Greater Options

- Factory- or Beld-installed, easy-to-read deluxe instrument panel.
- High-⊞ow auxiliary hydraulics to operate attachments requiring high hydraulic horsepower. such as planers and stump grinders.
- · Full suspension seat for all-day operator comfort.

Greater Value

Couple these features with proven power, smooth ride and vertical lift path capabilities and you've got a skid-steer loader that delivers top performance, no matter what the job. Get in the seat of a \$650 today for a great view and an even greater value!

S650

1220 kg

Rated Operating Capacity

3149 mm Lift Height

74-3 HP

Turbo-Charged, Liquid-Cooled Diesel Engine

Optional Deluxe Instrument Package Includes:

- Coolant Temperature & Oil Pressure
 Diagnostic Capability
 Help Screens
 System Voltage

- Engine RPM
 Digital and Job Clocks

- Shutdown Function Hydrostatic Charge Pressure
- Hydraulic Oil Temperature
 Engine/Hydraulic Systems
- - Keyless Start
 Multi-Language Display

 - · Password Lockout
 - · High Flow Lockout
 - Two-Speed Lockout

(SAE) and ISO standards. SpecIII cations and design are subject to change without notice. *Pletures of Bobcat loaders may show other than standard equipment, All dimensions are given for loader equipped with standard times. Bobcat Company compiles with the requirements of ISO goor as registered with BSI,

Operating capacity rated with standard digging bucket according to SAE standard 1818 OPERATING CAPACITY TO EQUAL NO MORE THAN ONE HALF THE TIP LOAD. 2 Hucket positioning helps operator keep the same tilt of the lo 3 Special applications kit (see #3) must be used.

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers

*Product improvement is a continuing goal at Doosan. Design and specifications are subject to change without notice or obligation.



Doosan Infracore

Doosan Infracore India Pvt. Ltd

3rd Floor, TNPL Building, No. 67, Mount Road, Guindy, Chennal - 600 032. Tel: +91 44 4222 3900/915, Fax: +91 44 4222 3905, Toll Free: 1800 200 2299 Email: marketingindia@doosan.com, www.doosaninfracore.com

Authorised Dealer

Doosan/B-S650/2P/E/201